

# KITSE1595\_PP\_68



MEDIA  
MEASURED  
LIQUIDS



PIPE DIAMETER  
FROM DN 80  
TO DN 4500



## SALES DESCRIPTION

- External probes for liquid flow measurement on a full pipe
- Standard applications - clear liquids and piping in good conditions
- Mounting on a pipe from DN80 to DN4500
- Maximum operating temperature of 80°C
- Push-Pull connectors

## INSTALLATION

Non intrusive

## APPLICATION

Full pipe

## CONDITIONS OF USE

Clear liquids, piping in good conditions

## PIPE DIAMETER

Recommended probe range: 100 - 3000 mm  
Extended probe range: 80 - 4500 mm (requires an 8XX converter)

## THICKNESS OF THE PIPE

> 1 mm

## CONNECTIC

Push - Pull connectors

## MOUNTING TYPE

/, V, N, W

## TEMPERATURE

From -20°C to +80°C

## SUPPORTS

Included

## COMPATIBLE CONVERTERS

ALL

## ATEX CERTIFICATION

NO

## INGRESS PROTECTION

EN/IEC 60529 IP68

## PROBE MATERIAL

Plexiglass

## OVERALL SIZE (support & probes)

500 x 50 x 100 mm

## OVERALL WEIGHT (support & probes)

1280 g

## SENSOR FREQUENCY

500 kHz